

Honeywell Performance
Materials and Technologies
has developed processes
and technology that enable
production of approximately
60% of the world's gasoline,
so it is no surprise that our
customers asked us to expand
the Research Chemical
portfolio of high-purity
solvents to include Primary
Reference Fuels (PRF).

Primary Reference Fuels

We have been a respected pioneer in solvents, inorganics, and other essential chemicals for over 200 years.

Octane number, the principal performance characteristic of gasoline, is determined through use of certified PRF fuels and a Cooperative Fuel Research (CFR) engine under controlled test conditions. Our PRF fuels are used in both research and analytical applications to provide outstanding results. Our history has influenced our growth as a company and our scientists and engineers build upon that heritage every day by developing products designed to meet the exacting specifications of a wide variety of different applications.

Quality

Product specifications are achieved through careful material selection and processing.

All PRF fuels in our portfolio undergo thorough quality control testing to ensure each lot conforms to the specifications defined in ASTM D2699 for Motor Octane Number (MON) and ASTM 2700 for Research Octane Number (RON). The results of this testing are summarized in a lot-specific Certificate of Analysis.

Consistency

You can depend upon our products working the first time and every time.

Our ISO 9001 and 14001 certified research and manufacturing facility located in Muskegon, Michigan benefits from the Honeywell Operating System, a comprehensive and integrated manufacturing approach based on Six Sigma and Lean Manufacturing methodologies, ensuring unparalleled batch-to-batch consistency.

Certified

Honeywell certifies that these products meet the requirements as defined in ASTM D2699 and D2700.

A precision study was conducted and samples were sent to Honeywell UOP's research lab as well as five respected independent third party laboratories. The data was compiled and run through a two sample t-test in Minitab®, with the results indicating there was no statistical difference between the lots sampled at the 95% confidence interval. The results are on file with the ASTM D02.01.0E committee.

| Product Number | Product Description | Package Info |
|----------------|---------------------|--------------|
| RS362-19 | Iso-octane | 19L Can |
| RS362-204 | Iso-octane | 204L Drum |
| RS347-19 | Toluene | 19L Can |
| RS347-204 | Toluene | 204L Drum |
| RS210-19 | n-Heptane | 19L Can |
| RS210-204 | n-Heptane | 204L Drum |
| RS2175-19 | 80 Octane Blend | 19L Can |
| RS2175-204 | 80 Octane Blend | 204L Drum |



Availability & Packaging Options

Honeywell, your trusted partner.

We hold strategic quantities of PRF inventory based upon forecasted demand. The PRF fuels are available in 55 gallon (204L) drums and 5 gallon (19L) cans.

We invite customers to contact our in-house technical experts to discuss custom blends of PRF fuels as well as special packaging requirements.

All statements and information provided herein are believed to be accurate and reliable, but are presented without guarantee, warranty or responsibility of any kind, express or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement, and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated herein, or that other measures may not be required. User assumes all liability for use of the information and results obtained.



Minitab is a registered trademark of Minitab, Inc.



