

HYDRANAL™ Coulomat CG**34840-50ML**

Version 1.3

Revision Date 05/01/2024

Print Date 05/02/2024

SECTION 1. IDENTIFICATION

Product name : HYDRANAL™ Coulomat CG

Number : 000000020625

Product Use Description : Laboratory chemicals, Scientific research and development

Manufacturer or supplier's details : Honeywell International Inc.
1953 South Harvey Street
Muskegon, MI 49442

For more information call : 1-800-368-0050
+1-231-726-3171 (Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414
: Transportation (CHEMTREC): 1-800-424-9300 or
+1-703-527-3887
:
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : liquid

Color : light yellow

Odor : aromatic

Classification of the substance or mixture

Classification of the substance or mixture : Flammable liquids, Category 2
Skin irritation, Category 2
Eye irritation, Category 2A
Specific target organ toxicity - single exposure, Category 1,
Eyes, Nervous system, Systemic toxicity

HYDRANAL™ Coulomat CG**34840-50ML**

Version 1.3

Revision Date 05/01/2024

Print Date 05/02/2024

GHS Label elements, including precautionary statements

Symbol(s)

:



Signal word

: Danger

Hazard statements

: Highly flammable liquid and vapour.
Causes skin irritation.
Causes serious eye irritation.
Causes damage to organs.

Precautionary statements

: **Prevention:**
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear protective gloves/protective clothing/eye protection/face protection.

Response:
IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed: Call a POISON CENTER or doctor/ physician.
If skin irritation occurs: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:
Store in a well-ventilated place. Keep cool.
Store locked up.

HYDRANAL™ Coulomat CG
34840-50ML

Version 1.3

Revision Date 05/01/2024

Print Date 05/02/2024

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture

Chemical name	CAS-No.	Concentration
Diethanolamine hydrochloride	14426-21-2	>=50.00 - <70.00 %
Methanol	67-56-1	>=30.00 - <50.00 %
Ethanol, 2,2'-iminobis-, hydriodide	134227-25-1	>=1.00 - <=5.00 %
Sulphur dioxide	7446-09-5	>=1.00 - <5.00 %

SECTION 4. FIRST AID MEASURES

- General advice : First aider needs to protect himself. Move out of dangerous area. Take off all contaminated clothing immediately.
- Inhalation : Move to fresh air. Keep patient warm and at rest. Call a physician immediately.
- Skin contact : Wash off immediately with plenty of water. If skin irritation persists, call a physician.
- Eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Protect unharmed eye.

HYDRANAL™ Coulomat CG**34840-50ML**

Version 1.3

Revision Date 05/01/2024

Print Date 05/02/2024

Ingestion : When swallowed, allow water to be drunk. Do NOT induce vomiting. Call a physician immediately.

Notes to physician

Most important symptoms/effects, acute and delayed : Inhalation may cause central nervous system effects. May be fatal or cause blindness if swallowed.

Indication of immediate medical attention and special treatment needed, if necessary : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray
Foam
Carbon dioxide (CO₂)
Dry powder

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

Specific hazards during firefighting : Flammable.
Vapours may form explosive mixtures with air.
Vapours are heavier than air and may spread along floors.
Vapors may travel to areas away from work site before igniting/flashing back to vapor source.
In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide
Carbon dioxide (CO₂)
Nitrogen oxides (NO_x)
Sulphur oxides
Hydrogen halides

Special protective equipment for firefighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

HYDRANAL™ Coulomat CG**34840-50ML**

Version 1.3

Revision Date 05/01/2024

Print Date 05/02/2024

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Wear personal protective equipment. Unprotected persons must be kept away.
Ensure adequate ventilation.
Remove all sources of ignition.
- Environmental precautions : Should not be released into the environment.
- Methods and materials for containment and cleaning up : Ventilate the area.
No sparking tools should be used.
Use explosion-proof equipment.
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE**Handling**

- Precautions for safe handling : Wear personal protective equipment.
Use only in well-ventilated areas.
- Advice on protection against fire and explosion : Keep away from sources of ignition - No smoking.
Take measures to prevent the build up of electrostatic charge.
The heavy vapours can overcome a considerable distance up to the source of ignition.
Vapours may form explosive mixtures with air.

Storage

- Conditions for safe storage, including any incompatibilities : Keep only in the original container, tightly closed, in a well ventilated place.
Store at room temperature.
(Ambient temperature: > 0 < 35°C)
Protect from atmospheric moisture and water.

HYDRANAL™ Coulomat CG
34840-50ML

Version 1.3

Revision Date 05/01/2024

Print Date 05/02/2024

Advice on common storage : Do not store together with:
Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Protective measures : Ensure that eyewash stations and safety showers are close to the workstation location.
Legal requirements are to be considered in regard of the selection, use and care of personal protective equipment.
Do not breathe vapours or spray mist.
- Engineering measures : Use with local exhaust ventilation.
Prevent vapour buildup by providing adequate ventilation during and after use.
- Eye protection : Safety goggles
- Hand protection : Impervious butyl rubber gloves
Gloves must be inspected prior to use.
Replace when worn.
- Skin and body protection : Protective suit
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
- Hygiene measures : General industrial hygiene practice.

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Update	Basis
Methanol	67-56-1	STEL : Short term exposure limit	325 mg/m ³ (250 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended

SAFETY DATA SHEET



HYDRANAL™ Coulomat CG

34840-50ML

Version 1.3

Revision Date 05/01/2024

Print Date 05/02/2024

Methanol	67-56-1	PEL : Permissible exposure limit	260 mg/m3 (200 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Methanol	67-56-1	STEL : Short term exposure limit	325 mg/m3 (250 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Methanol	67-56-1	TWA : Time weighted average	260 mg/m3 (200 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Methanol	67-56-1	TWA : Time weighted average	(200 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values, as amended
Methanol	67-56-1	REL : Recommended exposure limit (REL):	260 mg/m3 (200 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Methanol	67-56-1	SKIN_DES : Skin designation:	Can be absorbed through the skin.	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards, as amended

HYDRANAL™ Coulomat CG
34840-50ML

Version 1.3

Revision Date 05/01/2024

Print Date 05/02/2024

Methanol	67-56-1	SKIN_FINAL : Skin designation (Final Rule Limit applies):	Can be absorbed through the skin.	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Methanol	67-56-1	SKIN_DES : Skin designation:	Danger of cutaneous absorption	01 2020	ACGIH:US. ACGIH Threshold Limit Values, as amended
Methanol	67-56-1	STEL : Short term exposure limit	(250 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values, as amended
Sulphur dioxide	7446-09-5	TWA : Time weighted average	5 mg/m3 (2 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Sulphur dioxide	7446-09-5	REL : Recommended exposure limit (REL):	5 mg/m3 (2 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Sulphur dioxide	7446-09-5	STEL : Short term exposure limit	13 mg/m3 (5 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended

HYDRANAL™ Coulomat CG
34840-50ML

Version 1.3

Revision Date 05/01/2024

Print Date 05/02/2024

Sulphur dioxide	7446-09-5	STEL : Short term exposure limit	13 mg/m3 (5 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Sulphur dioxide	7446-09-5	PEL : Permissi ble exposure limit	13 mg/m3 (5 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Sulphur dioxide	7446-09-5	STEL : Short term exposure limit	(0.25 ppm)	2009	ACGIH:US. ACGIH Threshold Limit Values, as amended

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Color	: light yellow
Odor	: aromatic
Odor threshold	: Note: No data available
pH	: 4.0 - 7.0 at , 20 °C
Melting point/range	: Note: No data available
Boiling point/boiling range	: 63 °C at 1,013 hPa
Flash point	: 57 °F (14 °C)
Evaporation rate	: Note: No data available

HYDRANAL™ Coulomat CG**34840-50ML**

Version 1.3

Revision Date 05/01/2024

Print Date 05/02/2024

Lower explosion limit	: Note: No data available
Upper explosion limit	: Note: No data available
Vapor pressure	: Note: No data available
Vapor density	: Note: No data available
Density	: 1.064 g/cm ³ at 20 °C
Water solubility	: Note: completely miscible
Partition coefficient: n-octanol/water	: Note: No data available
Ignition temperature	: Note: No data available
Decomposition temperature	: Note: No decomposition if used as directed.
Viscosity, dynamic	: Note: No data available
Viscosity, kinematic	: Note: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous	: Vapours may form explosive mixture with air.

HYDRANAL™ Coulomat CG**34840-50ML**

Version 1.3

Revision Date 05/01/2024

Print Date 05/02/2024

reactions	Hazardous polymerisation does not occur.
Conditions to avoid	: Protect from atmospheric moisture and water. Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: In case of fire hazardous decomposition products may be produced such as: Carbon monoxide Carbon dioxide (CO ₂) Nitrogen oxides (NO _x) Sulphur oxides Hydrogen halides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity	: LD50: > 2,000 mg/kg Species: Rat
Acute inhalation toxicity Methanol	: LC50: 64000 ppm Exposure time: 4 h Species: Rat
Acute dermal toxicity Methanol	: LD50: 15,800 mg/kg Species: Rabbit
Skin irritation	: Note: The product has not been tested. The information is derived from the properties of the individual components.
Eye irritation	: Note: The product has not been tested. The information is derived from the properties of the individual components.

HYDRANAL™ Coulomat CG**34840-50ML**

Version 1.3

Revision Date 05/01/2024

Print Date 05/02/2024

Sensitisation	: Note: No data available
Repeated dose toxicity	: Note: The product has not been tested. The information is derived from the properties of the individual components.
Genotoxicity in vitro	: Note: No data available
Genotoxicity in vivo Methanol	: Note: In vivo tests did not show mutagenic effects

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity effects**

Toxicity to fish	: semi-static test LC50: > 1,000 mg/l Exposure time: 96 h Species: Leuciscus idus (Golden orfe) Method: OECD Test Guideline 203
	: NOEC: > 1,000 mg/l Species: Leuciscus idus (Golden orfe) Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : Note: No data available

Toxicity to bacteria : Growth inhibition
LC0: 275 mg/l
Species: Pseudomonas putida

Elimination information (persistence and degradability)

Biodegradability : Note: No data available

Further information on ecology

HYDRANAL™ Coulomat CG
34840-50ML

Version 1.3

Revision Date 05/01/2024

Print Date 05/02/2024

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Observe all Federal, State, and Local Environmental regulations.

SECTION 14. TRANSPORT INFORMATION

DOT	UN/ID No.	: UN 1230
	Proper shipping name	: METHANOL SOLUTION
	Class	: 3
	Packing group	: II
	Hazard Labels	: 3
IATA	UN/ID No.	: UN 1230
	Description of the goods	: METHANOL SOLUTION
	Class	: 3
	Packaging group	: II
	Hazard Labels	: 3 (6.1)
	Packing instruction (cargo aircraft)	: 364
	Packing instruction (passenger aircraft)	: 352
IMDG	UN/ID No.	: UN 1230
	Description of the goods	: METHANOL SOLUTION
	Class	: 3
	Packaging group	: II
	Hazard Labels	: 3 (6.1)
	EmS Number	: F-E, S-D
	Marine pollutant	: no
IMDG Code segregation group according chapter 3.1.4.4		: NONE,

SECTION 15. REGULATORY INFORMATION
Inventories

USA. List of Active : All chemical substances in this product are either listed on the

HYDRANAL™ Coulomat CG
34840-50ML

Version 1.3

Revision Date 05/01/2024

Print Date 05/02/2024

Substances on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory, as amended : TSCA Inventory or are in compliance with a TSCA Inventory exemption.

Australia. Inventory of Industrial Chemicals (AIIC), as amended : Not in compliance with the inventory

Canada. Domestic Substances List (DSL), as amended : Not in compliance with the inventory

Japan. Kashin-Hou Law List : Not in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI) : Not in compliance with the inventory

Philippines. Inventory of Chemicals and Chemical Substances (PICCS) : Not in compliance with the inventory

China. Inventory of Existing Chemical Substances (IECSC) : On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand : Not in compliance with the inventory

Note : Note: Because of the potential specific inventory listing of components of this product line, further, more detailed information can be requested from SafetyDataSheet@Honeywell.com.

Taiwan Chemical Substance Inventory (TCSI) : Not in compliance with the inventory

National regulatory information

TSCA : This material is in compliance with the TSCA Premanufacture Notification requirements specified in 40 CFR 720.30.

HYDRANAL™ Coulomat CG
34840-50ML

Version 1.3

Revision Date 05/01/2024

Print Date 05/02/2024

US. EPA CERCLA
Hazardous Substances (40
CFR 302)

:
: The following component(s) of this product is/are subject to
release reporting under 40 CFR 302 when release exceeds the
Reportable Quantity (RQ):

Reportable quantity: 5000 lbs

: Methanol 67-56-1

:

Reportable quantity: 500 lbs

: Sulphur dioxide 7446-09-5

SARA 302 Components

: The following components are subject to reporting levels
established by SARA Title III, Section 302:

: Sulphur dioxide 7446-09-5

SARA 313 Components

: The following components are subject to reporting levels
established by SARA Title III, Section 313:

: Methanol 67-56-1

SARA 311/312 Hazards

: Fire Hazard
Acute Health Hazard
Chronic Health Hazard

California Prop. 65

:



WARNING: This product can expose you to chemicals,
listed below, known to the State of California to cause birth
defects or other reproductive harm. For more information go to
www.P65Warnings.ca.gov.

Sulphur dioxide 7446-09-5

Methanol 67-56-1

Massachusetts RTK

: Methanol 67-56-1

: Sulphur dioxide 7446-09-5

New Jersey RTK

: Methanol 67-56-1

: Sulphur dioxide 7446-09-5

Pennsylvania RTK

: Methanol 67-56-1

: Sulphur dioxide 7446-09-5

HYDRANAL™ Coulomat CG
34840-50ML

Version 1.3

Revision Date 05/01/2024

Print Date 05/02/2024

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 2*	2
Flammability	: 3	3
Physical Hazard	: 0	
Instability	:	0

* - Chronic health hazard

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 03/02/2020

Prepared by Honeywell Energy and Sustainability Solutions Product Stewardship Group Product Stewardship Group