

HYDRANAL™ Coulomat Oil**34868-100ML**

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

SECTION 1. IDENTIFICATION

Product name : HYDRANAL™ Coulomat Oil

Number : 000000020629

Product Use Description : Laboratory chemicals
Scientific research and development

Manufacturer or supplier's details : Honeywell International Inc.
1953 South Harvey Street
Muskegon, MI 49442

For more information call : 1-800-368-0050
+1-231-726-3171 (Monday-Friday, 9:00am-5:00pm)

In case of emergency call : **Medical: 1-800-498-5701 or +1-303-389-1414**
: **Transportation (CHEMTREC): 1-800-424-9300 or**
: **+1-703-527-3887**
:
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : liquid

Color : colourless

Odor : characteristic

Classification of the substance or mixture

Classification of the substance or mixture : Flammable liquids, Category 2
Acute toxicity, Category 4, Oral
Acute toxicity, Category 4, Inhalation
Skin corrosion, Category 1B
Serious eye damage, Category 1
Carcinogenicity, Category 2

HYDRANAL™ Coulomat Oil**34868-100ML**

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

Reproductive toxicity, Category 1B
Specific target organ toxicity - single exposure, Category 1,
Eyes, Nervous system, Systemic toxicity
Specific target organ toxicity - single exposure, Category 3,
Respiratory system, Central nervous system
Specific target organ toxicity - repeated exposure, Category 1,
Liver, Kidney
Aspiration hazard, Category 1

GHS Label elements, including precautionary statements

Symbol(s)

:



Signal word

: Danger

Hazard statements

: Highly flammable liquid and vapour.
Harmful if swallowed or if inhaled.
May be fatal if swallowed and enters airways.
Causes severe skin burns and eye damage.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Suspected of causing cancer.
May damage fertility or the unborn child.
Causes damage to organs.
Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

: **Prevention:**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Do not eat, drink or smoke when using this product.

HYDRANAL™ Coulomat Oil**34868-100ML**

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

Use only outdoors or in a well-ventilated area.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/ doctor.

Wash contaminated clothing before reuse.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity

NTP: Chloroform 67-66-3

Reasonably Anticipated to be a Human Carcinogen.

IARC: Chloroform 67-66-3

Group 2B: Possibly carcinogenic to humans

ACGIH: Chloroform 67-66-3

A3: Confirmed animal carcinogen

HYDRANAL™ Coulomat Oil**34868-100ML**

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture

Chemical name	CAS-No.	Concentration
Methanol	67-56-1	>=30.00 - <50.00 %
o-Xylene	95-47-6	>=20.00 - <30.00 %
Chloroform	67-66-3	>=20.00 - <30.00 %
1H-Imidazole monohydriodide	68007-08-9	>=10.00 - <20.00 %
Imidazole	288-32-4	>=1.00 - <5.00 %
Sulphur dioxide	7446-09-5	>=1.00 - <5.00 %

SECTION 4. FIRST AID MEASURES

- General advice : First aider needs to protect himself. Move out of dangerous area. Take off all contaminated clothing immediately.
- Inhalation : Remove to fresh air. Keep patient warm and at rest. Call a physician immediately.
- Skin contact : Wash off immediately with plenty of water. If skin irritation persists, call a physician.
- Eye contact : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Protect unharmed eye.
- Ingestion : Immediately give large quantities of water to drink. Do NOT induce vomiting. Call a physician immediately.

HYDRANAL™ Coulomat Oil**34868-100ML**

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

Notes to physician

Most important symptoms/effects, acute and delayed : No information available.

Indication of immediate medical attention and special treatment needed, if necessary : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide (CO₂)
Dry chemical
Dry powder
Water spray

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

Specific hazards during firefighting : Flammable.
Vapours may form explosive mixtures with air.
Vapours are heavier than air and may spread along floors.
Vapors may travel to areas away from work site before igniting/flashing back to vapor source.
In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide
Carbon dioxide (CO₂)
Formaldehyde
Phosgene
Nitrogen oxides (NO_x)
Sulphur oxides
Hydrogen halides

Special protective equipment for firefighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

HYDRANAL™ Coulomat Oil**34868-100ML**

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | | |
|---|---|--|
| Personal precautions,
protective equipment and
emergency procedures | : | Evacuate personnel to safe areas.
Wear personal protective equipment. Unprotected persons
must be kept away.
Remove all sources of ignition.
Ensure adequate ventilation. |
| Environmental precautions | : | Should not be released into the environment. |
| Methods and materials for
containment and cleaning
up | : | Ventilate the area.
No sparking tools should be used.
Use explosion-proof equipment.
Contain spillage, soak up with non-combustible absorbent
material, (e.g. sand, earth, diatomaceous earth, vermiculite) and
transfer to a container for disposal according to local / national
regulations (see section 13). |

SECTION 7. HANDLING AND STORAGE**Handling**

- | | | |
|--|---|--|
| Precautions for safe
handling | : | Wear personal protective equipment.
Use only in well-ventilated areas. |
| Advice on protection against
fire and explosion | : | Keep away from sources of ignition - No smoking.
Take measures to prevent the build up of electrostatic charge.
The heavy vapours can overcome a considerable distance up to
the source of ignition.
Vapours may form explosive mixtures with air. |

Storage

- | | | |
|--|---|--|
| Conditions for safe storage,
including any
incompatibilities | : | Keep only in the original container, tightly closed, in a well
ventilated place.
Store at room temperature.
(Ambient temperature: > 0 < 35°C)
Protect from atmospheric moisture and water. |
|--|---|--|

HYDRANAL™ Coulomat Oil**34868-100ML**

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Protective measures : Ensure that eyewash stations and safety showers are close to the workstation location.
Legal requirements are to be considered in regard of the selection, use and care of personal protective equipment.
Do not breathe vapours or spray mist.
- Engineering measures : Use with local exhaust ventilation.
Prevent vapour buildup by providing adequate ventilation during and after use.
- Eye protection : Safety goggles
- Hand protection : Impervious gloves
Gloves must be inspected prior to use.
Replace when worn.
- Skin and body protection : Protective suit
- Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment.
Recommended Filter type:
Organic gas and low boiling vapour type
- Hygiene measures : Take off all contaminated clothing immediately.
Remove and wash contaminated clothing before re-use.
Wash hands before breaks and at the end of workday.
When using do not eat or drink.

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Update	Basis
Methanol	67-56-1	TWA : Time weighted average	(200 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values, as amended
Methanol	67-56-1	SKIN_DES : Skin designation:	Danger of cutaneous absorption	01 2020	ACGIH:US. ACGIH Threshold Limit Values, as amended

SAFETY DATA SHEET



HYDRANAL™ Coulomat Oil

34868-100ML

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

Methanol	67-56-1	STEL : Short term exposure limit	(250 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values, as amended
Methanol	67-56-1	SKIN_DE S : Skin designati on:	Can be absorbed through the skin.	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Methanol	67-56-1	REL : Recomm ended exposure limit (REL):	260 mg/m3 (200 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Methanol	67-56-1	STEL : Short term exposure limit	325 mg/m3 (250 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Methanol	67-56-1	PEL : Permissi ble exposure limit	260 mg/m3 (200 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Methanol	67-56-1	TWA : Time weighted average	260 mg/m3 (200 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended

SAFETY DATA SHEET



HYDRANAL™ Coulomat Oil

34868-100ML

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

Methanol	67-56-1	STEL : Short term exposure limit	325 mg/m3 (250 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Methanol	67-56-1	SKIN_FI NAL : Skin designati on (Final Rule Limit applies):	Can be absorbed through the skin.	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
o-Xylene	95-47-6	STEL : Short term exposure limit	(150 ppm)	03 2014	ACGIH:US. ACGIH Threshold Limit Values, as amended
o-Xylene	95-47-6	TWA : Time weighted average	(100 ppm)	03 2014	ACGIH:US. ACGIH Threshold Limit Values, as amended
o-Xylene	95-47-6	TWA : Time weighted average	(20 ppm)	01 2021	ACGIHLIS_P:US. ACGIH Notice of Intended Changes (NIC) to Threshold Limit Values, as amended
o-Xylene	95-47-6	STEL : Short term exposure limit	655 mg/m3 (150 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards, as amended

SAFETY DATA SHEET

**HYDRANAL™ Coulomat Oil****34868-100ML**

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

o-Xylene	95-47-6	REL : Recomm ended exposure limit (REL):	435 mg/m3 (100 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards, as amended
o-Xylene	95-47-6	PEL : Permissi ble exposure limit	435 mg/m3 (100 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
o-Xylene	95-47-6	TWA : Time weighted average	435 mg/m3 (100 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
o-Xylene	95-47-6	STEL : Short term exposure limit	655 mg/m3 (150 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Chloroform	67-66-3	TWA : Time weighted average	(10 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values, as amended
Chloroform	67-66-3	STEL : Short term exposure limit	9.78 mg/m3 (2 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards, as amended

SAFETY DATA SHEET



HYDRANAL™ Coulomat Oil

34868-100ML

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

Chloroform	67-66-3	Ceiling : Ceiling Limit Value:	240 mg/m3 (50 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Chloroform	67-66-3	TWA : Time weighted average	9.78 mg/m3 (2 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Sulphur dioxide	7446-09-5	STEL : Short term exposure limit	(0.25 ppm)	2009	ACGIH:US. ACGIH Threshold Limit Values, as amended
Sulphur dioxide	7446-09-5	REL : Recomm ended exposure limit (REL):	5 mg/m3 (2 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Sulphur dioxide	7446-09-5	STEL : Short term exposure limit	13 mg/m3 (5 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Sulphur dioxide	7446-09-5	PEL : Permissi ble exposure limit	13 mg/m3 (5 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended

HYDRANAL™ Coulomat Oil**34868-100ML**

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

Sulphur dioxide	7446-09-5	TWA : Time weighted average	5 mg/m3 (2 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Sulphur dioxide	7446-09-5	STEL : Short term exposure limit	13 mg/m3 (5 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Color	: colourless
Odor	: characteristic
Odor threshold	: Note: No data available
pH	: 5 - 6
Melting point/range	: Note: No data available
Boiling point/boiling range	: Note: No data available
Flash point	: 46 °F (8 °C) Method: closed cup
Evaporation rate	: Note: No data available
Lower explosion limit	: Note: No data available
Upper explosion limit	: Note: No data available

HYDRANAL™ Coulomat Oil**34868-100ML**

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

Vapor pressure	: Note: No data available
Vapor density	: Note: No data available
Density	: 1.042 g/cm ³ at 20 °C
Water solubility	: Note: insoluble
Partition coefficient: n-octanol/water	: Note: No data available
Ignition temperature	: Note: No data available
Decomposition temperature	: Note: No decomposition if used as directed.
Viscosity, dynamic	: Note: No data available
Viscosity, kinematic	: Note: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. Hazardous polymerisation does not occur.
Conditions to avoid	: Protect from moisture. Heat, flames and sparks.
Incompatible materials	: Zinc Strong bases

HYDRANAL™ Coulomat Oil**34868-100ML**

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

Acids
Oxidizing agents
Acid chlorides
Acid anhydrides
Reducing agents
Alkali metals

Hazardous decomposition
products

: In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide
Carbon dioxide (CO₂)
Formaldehyde
Phosgene
Nitrogen oxides (NO_x)
Sulphur oxides
Hydrogen halides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

: Acute toxicity estimate: 1,307 mg/kg
Method: Calculation method

Acute inhalation toxicity

: Acute toxicity estimate: 6760 ppm, gas
Exposure time: 4 h
Method: Calculation method

Acute dermal toxicity

: Acute toxicity estimate: 4,314 mg/kg
Method: Calculation method

Skin irritation

: Species: Rabbit
Result: Causes severe burns.
Classification: Corrosive

Eye irritation

: Result: Risk of serious damage to eyes.
Note: The product has not been tested. The information is derived from the properties of the individual components.

HYDRANAL™ Coulomat Oil**34868-100ML**

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

Sensitisation
1H-Imidazole
monohydriodide

: Mouse local lymph node assay
Species: Mouse
Result: Does not cause skin sensitisation.
Method: OECD 429

Repeated dose toxicity

: Note: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2. The product has not been tested. The information is derived from the properties of the individual components.

Genotoxicity in vitro

: Note: The product has not been tested. The information is derived from the properties of the individual components.

Genotoxicity in vivo
Methanol

: Note: In vivo tests did not show mutagenic effects

Imidazole

: Test Method: Micronucleus test
Species: Mouse, male and female
Cell type: Bone marrow
Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

Aspiration toxicity

: May be fatal if swallowed and enters airways. The product has not been tested. The information is derived from the properties of the individual components.

Teratogenicity
1H-Imidazole
monohydriodide

: Test Method: reproductive and developmental toxicity study
Species: Rat
Result: Teratogenic effects
Note: Not a GLP Study.

Imidazole

: Species: Rat Application Route: Oral

No observed adverse effect level: 60 mg/kg body weight

HYDRANAL™ Coulomat Oil**34868-100ML**

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

No observed adverse effect level: 60 mg/kg body weight
Method: OECD Test Guideline 414
Result: Embryotoxic effects and adverse effects on the offspring were detected.

Further information

Chloroform

: Note:
Contains material which may cause cancer based on animal data.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity to fish

Methanol

: LC50: 29,400 mg/l
Exposure time: 96 h
Species: Pimephales promelas (fathead minnow)

o-Xylene

: LC50: 16.9 mg/l
Exposure time: 96 h
Species: Carassius auratus (goldfish)

Chloroform

: static test
LC50: 43.8 mg/l
Exposure time: 96 h
Species: Oncorhynchus mykiss (rainbow trout)

static test
LC50: 100 mg/l
Exposure time: 96 h
Species: Lepomis macrochirus (Bluegill sunfish)

1H-Imidazole
monohydriodide

: LC0: ≥ 100 mg/l
Exposure time: 96 h
Species: Danio rerio (zebra fish)
Method: OECD Test Guideline 203

Imidazole

: static test
LC50: 283.6 mg/l
Exposure time: 48 h
Species: Leuciscus idus (Golden orfe)

HYDRANAL™ Coulomat Oil**34868-100ML**

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

Toxicity to daphnia and other aquatic invertebrates

Methanol : LC50: 10,000 mg/l
Exposure time: 24 h
Species: Daphnia (water flea)

Chloroform : static test
LC50: 28.9 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)

1H-Imidazole monohydriodide : EC50: 1.4 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 202

EC0: 0.46 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 202

Imidazole : static test
EC50: 341.5 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae

Chloroform : LC0: 185 mg/l
Species: Microcystis aeruginosa (blue alge)

LC0: 1,110 mg/l
Species: Scenedesmus quadricauda

1H-Imidazole monohydriodide : Biomass
EC50: 8.3 mg/l
Exposure time: 72 h
Species: scenedesmus subspicatus
Method: OECD Test Guideline 201

Growth rate
EC50: 34 mg/l
Exposure time: 72 h
Species: scenedesmus subspicatus

HYDRANAL™ Coulomat Oil**34868-100ML**

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

Method: OECD Test Guideline 201

Biomass

NOEC: 1 mg/l

Exposure time: 72 h

Species: scenedesmus subspicatus

Method: OECD Test Guideline 201

Biomass

NOEC: 1 mg/l

Exposure time: 72 h

Species: scenedesmus subspicatus

Method: OECD Test Guideline 201

Imidazole

: static test

EC50: 133 mg/l

Exposure time: 72 h

Species: Desmodesmus subspicatus (green algae)

Method: DIN 38412

Toxicity to bacteria

Methanol

: EC50: 43,000 mg/l

Exposure time: 5 min

Species: Photobacterium phosphoreum

EC50: 40,000 mg/l

Exposure time: 15 min

Species: Photobacterium phosphoreum

EC50: 39,000 mg/l

Exposure time: 25 min

Species: Photobacterium phosphoreum

Chloroform

: LC0: 125 mg/l

Species: Pseudomonas putida

1H-Imidazole
monohydriodide

: Respiration inhibition

EC50: > 1,000 mg/l

Exposure time: 3 h

Species: activated sludge

Method: OECD 209

Respiration inhibition

NOEC: 320 mg/l

HYDRANAL™ Coulomat Oil**34868-100ML**

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

Exposure time: 3 h
Species: activated sludge
Method: OECD 209

Biodegradability
Imidazole

: Result: Readily biodegradable.
Method: OECD Test Guideline 301A

Further information on ecology

Additional ecological
information : Should not be released into the environment.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Observe all Federal, State, and Local Environmental regulations.

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 3286
Proper shipping name : FLAMMABLE LIQUID, TOXIC, CORROSIVE,
N.O.S.
(Methanol, Chloroform, Imidazole)
Class : 3
Packing group : II
Hazard Labels : 3 (6.1, 8)

IATA UN/ID No. : UN 3286
Description of the goods : FLAMMABLE LIQUID, TOXIC, CORROSIVE,
N.O.S.
(Methanol, Chloroform, Imidazole)
Class : 3
Packaging group : II
Hazard Labels : 3 (6.1, 8)
Packing instruction (cargo aircraft) : 363
Packing instruction (passenger aircraft) : 352
Packing instruction : Y340

HYDRANAL™ Coulomat Oil**34868-100ML**

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

(passenger aircraft)

IMDG	UN/ID No.	: UN 3286
	Description of the goods	: FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (METHANOL, CHLOROFORM, IMIDAZOLE)
	Class	: 3
	Packaging group	: II
	Hazard Labels	: 3 (6.1, 8)
	EmS Number	: F-E, S-C
	Marine pollutant	: no
	IMDG Code segregation group (SGG10)	– Liquid halogenated hydrocarbons,

SECTION 15. REGULATORY INFORMATION**Inventories**

US. Toxic Substances Control Act	: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
Australia. Inventory of Industrial Chemicals (AIIC), as amended	: On the inventory, or in compliance with the inventory
China. Inventory of Existing Chemical Substances (IECSC)	: On the inventory, or in compliance with the inventory
Taiwan Chemical Substance Inventory (TCSI)	: Not in compliance with the inventory

National regulatory information


TSCA	: This material must be used in compliance with the TSCA Research and Development Exemption requirements (40 CFR 720.36).
US. EPA CERCLA Hazardous Substances (40 CFR 302)	: : The following component(s) of this product is/are subject to release reporting under 40 CFR 302 when release exceeds the Reportable Quantity (RQ): Reportable quantity: 10 lbs

HYDRANAL™ Coulomat Oil
34868-100ML

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

	:	Chloroform	67-66-3
	:		
	:	Reportable quantity: 1000 lbs	
	:	o-Xylene	95-47-6
	:		
	:	Reportable quantity: 5000 lbs	
	:	Methanol	67-56-1
	:		
	:	Reportable quantity: 500 lbs	
	:	Sulphur dioxide	7446-09-5
SARA 302 Components	:	The following components are subject to reporting levels established by SARA Title III, Section 302:	
	:	Sulphur dioxide	7446-09-5
	:	Chloroform	67-66-3
SARA 313 Components	:	The following components are subject to reporting levels established by SARA Title III, Section 313:	
	:	Methanol	67-56-1
	:	o-Xylene	95-47-6
	:	Chloroform	67-66-3
SARA 311/312 Hazards	:	Fire Hazard Acute Health Hazard Chronic Health Hazard	
CERCLA Reportable Quantity	:	40 lbs	
California Prop. 65	:	 WARNING: This product can expose you to chemicals, listed below, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov .	
		Chloroform	67-66-3
		Methanol	67-56-1
		Chloroform	67-66-3
		Sulphur dioxide	7446-09-5
Massachusetts RTK	:	Methanol	67-56-1
	:	o-Xylene	95-47-6
	:	Chloroform	67-66-3
	:	Sulphur dioxide	7446-09-5
New Jersey RTK	:	Sulphur dioxide	7446-09-5

HYDRANAL™ Coulomat Oil**34868-100ML**

Version 3.1

Revision Date 05/09/2023

Print Date 05/12/2023

	: Chloroform	67-66-3
	: o-Xylene	95-47-6
	: Methanol	67-56-1
Pennsylvania RTK	: Methanol	67-56-1
	: o-Xylene	95-47-6
	: Chloroform	67-66-3
	: Sulphur dioxide	7446-09-5

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 3*	3
Flammability	: 3	3
Physical Hazard	: 0	
Instability	:	0

* - Chronic health hazard

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 01/12/2022

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group